

# 810 LC Clamshell Lathe

4 to 10 inches (114 to 273mm) Nominal Bore

Mactech Europe offer portable pipe cutting machines for On-Site precision cutting and bevelling of most pipe sizes, schedules and materials.

The Clamshell Lathes cover a wide range of pipe sizes from 2" to 110" Nominal Bore and are designed so that minimal radial and axial clearance are required for easy installation on in-line closed loop pipe.

Unlike other competitive cold cutters our lathes have more bearings making it the most versatile machine in the industry to cut and bevel pipe, re-machine flanges, machine shafts and more.



## Benefits

- Sever or simultaneous Sever / Bevell 4" to 10" Nominal Bore.
- Cold Cutting in hazardous environments.
- Exceptionally rigid, split-frame for precise on-site machining.
- Tool Holder accepts standard 3/4" or 1" tool bits.
- Lightweight, low clearance design for easy handling in tight workspaces.
- Air Caddy (air filter & oiler) included with air drive systems
- Customer setups and drives available for your application.




Mactech (Europe) Ltd  
Mactech House  
Riverdane Road  
Eaton Bank Trading Estate  
Congleton  
Cheshire  
CW12 1PN  
+ 44 (0) 1260 281431

Mactech (Europe) Ltd.  
Mactech House  
Howe Moss Drive  
Dyce  
Aberdeen  
Scotland  
AB21 0GL  
+ 44 (0) 1224 722666

Mactech (Europe) BV  
Moerbeij 16  
3371 NZ  
Hardinxveld-Giessendam  
Netherlands  
+31 (0) 184 633 953

# 810 LC Clamshell Lathe

4 to 10 inches (114 to 273mm) Nominal Bore



LC CLAMSHELL PORTABLE LATHE DIMENSIONS

Dimensions	804 LC	806 LC	808 LC	810 LC	812 LC	814 LC	816 LC
A - Machine I.D	5.00" (127.0mm)	7.12" (180.8mm)	9.12" (231.6mm)	11.25" (285.7mm)	13.25" (336.5mm)	14.50" (368.3mm)	16.50" (419.1mm)
B - Machine O.D	9.98" (253.5mm)	12.10" (307.3mm)	14.10" (358.1mm)	16.22" (411.9mm)	18.21" (462.5mm)	19.48" (494.7mm)	21.48" (545.5mm)
C - # 3 Slides	12.75" (323.8mm)	14.87" (377.7mm)	16.87" (428.5mm)	19.0" (482.6mm)	21.00" (533.4mm)	22.25" (565.1)	24.25" (615.9mm)
D - # 4 Slides	14.75" (374.6mm)	16.87" (428.4mm)	18.87" (479.2mm)	21.00" (533.4mm)	23.00" (584.2mm)	24.25" (615.9mm)	26.25" (666.75mm)

# 810 LC Clamshell Lathe

4 to 10 inches (114 to 273mm) Nominal Bore

## LC CLAMSHELL PORTABLE LATHE SPECIFICATIONS

Application Range	4 to 10 inches (114 to 273mm) Nominal Bore	
Feed	Feed Mechanism	7 Point Star Wheel & Tripper
	Feed Rate	.0035" (0.09 mm) per revolution
Drives	<ul style="list-style-type: none"><li>Air Drive Requirement 100cfm @ 100 psi (2.8m3/min @ 6.9 bar)</li></ul>	
	<ul style="list-style-type: none"><li>Hydraulic Drive HPU Requirement 10-15 gpm @1000 psi (38-57lpm@69 bar) continuous pressure - includes hose whips and quick connects</li></ul>	
Weights	Operating Weights include tool blocks, slides and drive motor 810LC Air Drive 88lbs (40kg)   810LC Hydraulic Drive 92lbs (42kg)	
	Shipping Weights includes equipment and shipping crate 810LC Air Drive 177lbs (80kg)   810LC Hydraulic Drive 168lbs (76kg)	
Options	Full line of tool bits   Right angle & reversible drives   Single point machining attachment   Axial Feed Machining attachment   Counterbore / Facing attachment   Hydraulic Power Unit	
Frame	The aluminium frame is a split ring assembly capable of being disassembled to be installed around in-line piping. The frame has bearing mountings for the rotating head, a drive motor mount, locator pads for mounting to the pipe, and a gear cover.	
Cutting Head Assembly	The cutting head assembly is a heat treated 4140 alloy steel split ring gear assembly, which aligns with the split lines of the frame enabling the machine to be split in half. The cutting head has an integral spur gear on the outside diameter, and mounting devices for tool holders.	
Drive Assembly	The drive motor assembly mounts to the frame and is arranged with a pinion gear on a shaft. The drive motor mount bracket is designed to accept the reaction torque generated by the drive motor.	
Bearings	The cutting head runs on precision bearings that provide for both axial and radial force reactions experienced in pipe machining. Mactech utilises two separate radial bearing arrangements in every machine, providing maximum rigidity of operation. They are designed so that adjustments are not required.	
Tool Holder (blocks)	The tool holders mounted to the cutting head assembly are provided with automatic radial feed "star wheel" mechanisms. They are designed to maintain the radial clearance equal to the frame diameter and feature adjustable gibs for tool support.	
Locator Pads	Adjustable locator pads are actuated by jackscrews from the outside of the frame. A set of locator pads with extensions to cover the machine's operating range is provided with each machine. Additional sizes for each machine are available.	
Tool Bits	Mactech tool bits are available for severing, severing and double bevelling, severing and bevelling on the side of the cut on which the clamshell is mounted (right hand), severing and bevelling on the opposite side of the cut (left hand), counterboring, socket weld removal, etc.	